

Safety Data Sheet
 per OSHA HazCom 2012

1 Identification

Product identifier

Product name: Barium tungsten isopropoxide, 10% inisopropanol

Stock number: 41046

CAS Number:
 333971-25-8

Relevant identified uses of the substance or mixture and uses advised against.
Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar
 Thermo Fisher Scientific Chemicals, Inc.
 30 Bond Street
 Ward Hill, MA 01835-8099
 Tel: 800-343-0660
 Fax: 800-322-4757
 Email: tech@alfa.com
 www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)

 GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

 GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H336 May cause drowsiness or dizziness.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapor.

H302+H332 Harmful if swallowed or if inhaled.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P302+P352 IF ON SKIN: Wash with plenty of water/...

WHMIS classification

B2 - Flammable liquid



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 1 Health (acute effects) = 1

FIRE 3 Flammability = 3

REACTIVITY 1 Physical Hazard = 1

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Substances

CAS# Description:

333971-25-8 Barium tungsten isopropoxide, 10% inisopropanol

4 First-aid measures

Description of first aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek medical treatment.

Product name: Barium tungsten isopropoxide, 10% inisopropanol

(Contd. of page 1)

Information for doctor

Most important symptoms and effects, both acute and delayed No further relevant information available.
Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
Special hazards arising from the substance or mixture
If this product is involved in a fire, the following can be released:
Carbon monoxide and carbon dioxide
Barium oxide
Metal oxide fume
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow material to be released to the environment without proper governmental permits.
Methods and material for containment and cleaning up:
Keep away from ignition sources.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Prevention of secondary hazards: Keep away from ignition sources.
Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

Handling
Precautions for safe handling
Handle under dry protective gas.
Handle under protective gas.
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Information about protection against explosions and fires:
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away.
Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility:
Store away from oxidizing agents.
Store away from water/moisture.
Further information about storage conditions:
Store under dry inert gas.
This product is moisture sensitive.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Protect from humidity and water.
Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

Barium, and soluble compounds, as Ba
mg/m³
ACGIH TLV 0.5; Not classified as a human carcinogen
Austria MAK 0.5
Belgium TWA 0.5
Denmark TWA 0.5
Finland TWA 0.5
Germany MAK 0.5 (total dust)
Hungary 0.5-STEEL
Ireland TWA 0.5
Korea TLV 0.5
Netherlands MAC-TGG 0.5
Norway TWA 0.5
Poland TWA 0.5; 1.5-STEEL
Sweden TWA 0.5
Switzerland MAK-W 0.5
United Kingdom LTEL 0.5
USA PEL 0.5

Tungsten and compounds (as W)
mg/m³
ACGIH TLV 5; 10-STEEL (metal)
1; 3-STEEL (soluble compounds)
5; 10-STEEL (insoluble compounds)
Belgium TWA 1 (soluble compounds)
5; 10-STEEL (insoluble compounds)

(Contd. on page 3)
USA

Product name: Barium tungsten isopropoxide, 10% inisopropanol

(Contd. of page 2)

Finland TWA 5 (metal)
1 (soluble compounds)
5 (insoluble compounds)
Netherlands MAC-TGG 5 (metal)
1 (soluble compounds)
5 (insoluble compounds)
Poland TWA 5 (metal)
1 (soluble compounds)
5 (insoluble compounds)
Sweden NGV 5 (metal)
1 (soluble compounds)
5 (insoluble compounds)
United Kingdom TWA 5; 10-STEEL (metal)
1; 3-STEEL (soluble compounds)
5; 10-STEEL (insoluble compounds)
MSHA TWA 1 (soluble compounds)
5 (insoluble compounds)

Isopropyl alcohol (2-Propanol)
ppm
ACGIH TLV 400; 500-STEEL
Austria MAK 400
Belgium TWA 400; 500-STEEL
Denmark TWA 200
France VLE 400
Germany MAK 400
Ireland TWA 400; 500-STEEL (skin)
Japan TWA 400-STEEL
Korea TWA 400; 500-STEEL
Netherlands MAC-TGG 400 (skin)
Norway TWA 100
Poland TWA 900; 1200-STEEL
Russia TWA 400-STEEL
Sweden NGV 150; 250-STEEL
Switzerland MAK-W 400
United Kingdom TWA 400; 500-STEEL
OSHA PEL 400

Additional information: No data

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection: Safety glasses

Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid
Color: Yellow
Odor: Alcohol-like
Odor threshold: Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range: Not determined
Boiling point/Boiling range: Not determined
Sublimation temperature / start: Not determined

Flash point: 12 °C (54 °F) (i-PrOH)
Flammability (solid, gaseous): Not determined.
Ignition temperature: Not determined
Decomposition temperature: Not determined
Auto igniting: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures is possible.

Explosion limits:

Lower: Not determined
Upper: Not determined
Vapor pressure: Not determined
Density: Not determined
Relative density: Not determined.
Vapor density: Not determined.
Evaporation rate: Not determined.

Solubility in / Miscibility with

Water: Hydrolyzes
Partition coefficient (n-octanol/water): Not determined.

Viscosity:

dynamic: Not determined.
kinematic: Not determined.

Other information No further relevant information available.

Product name: **Barium tungsten isopropoxide, 10% inisopropanol**

(Contd. of page 3)

10 Stability and reactivity

Reactivity No information known.
Chemical stability Stable under recommended storage conditions.
Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.
Possibility of hazardous reactions No dangerous reactions known
Conditions to avoid No further relevant information available.
Incompatible materials:
 Oxidizing agents
 Water/moisture
Hazardous decomposition products:
 Carbon monoxide and carbon dioxide
 Metal oxide fume
 Barium oxide

11 Toxicological information

Information on toxicological effects
Acute toxicity:
 Harmful if inhaled.
 Harmful if swallowed.
LD/LC50 values that are relevant for classification: No data
Skin irritation or corrosion: May cause irritation
Eye irritation or corrosion: May cause irritation
Sensitization: No sensitizing effects known.
Germ cell mutagenicity: No effects known.
Carcinogenicity:
 IARC-3: Not classifiable as to carcinogenicity to humans.
 ACGIH A4: Not classifiable as a human carcinogen: Inadequate data on which to classify the agent in terms of its carcinogenicity in humans and/or animals.
Reproductive toxicity: No effects known.
Specific target organ system toxicity - repeated exposure: No effects known.
Specific target organ system toxicity - single exposure:
 May cause drowsiness or dizziness.
 May cause respiratory irritation.
Aspiration hazard: No effects known.
Subacute to chronic toxicity:
 Barium compounds may cause severe gastroenteritis, including abdominal pain, vomiting and diarrhea, tremors, faintness, paralysis of the arms and legs, and slow or irregular heartbeat. Severe cases may produce collapse and death due to respiratory failure. Soluble barium compounds are more likely to cause these effects than insoluble compounds. Inhalation of fumes may cause sore throat, coughing, labored breathing, and irritation of the respiratory tract as well as the above symptoms.
 Tungsten compounds may be irritating to the eyes and respiratory tract. Chronic exposure may result in permanent lung damage.
 2-Propanol (isopropyl alcohol) may act as a local irritant and in high concentrations as a narcotic with symptoms such as headache, nausea, dizziness, vomiting, mental depression, anesthesia, and coma. Similar symptoms may be caused by ingestion. It can cause corneal burns on contact with the eyes and has caused teratogenic, mutagenic and reproductive effects in laboratory animals.
Subacute to chronic toxicity: No effects known.
Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

12 Ecological information

Toxicity
Aquatic toxicity: No further relevant information available.
Persistence and degradability No further relevant information available.
Bioaccumulative potential No further relevant information available.
Mobility in soil No further relevant information available.
Additional ecological information:
General notes:
 Do not allow material to be released to the environment without proper governmental permits.
 Do not allow undiluted product or large quantities to reach ground water, water course or sewage system.
 Avoid transfer into the environment.
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods
Recommendation Consult state, local or national regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number DOT, IMDG, IATA	UN1219
UN proper shipping name DOT IMDG, IATA	Isopropanol (Isopropyl alcohol) ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport hazard class(es) DOT	
	
Class	3 Flammable liquids.
Label	3
Class	3 (F1) Flammable liquids
Label	3

(Contd. on page 5)
USA

Product name: **Barium tungsten isopropoxide, 10% inisopropanol**

(Contd. of page 4)

IMDG, IATA



Class 3 Flammable liquids.
Label 3

Packing group II
DOT, IMDG, IATA

Environmental hazards: Not applicable.

Special precautions for user Warning: Flammable liquids
EMS Number: F-E, S-D

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT
Marine Pollutant (DOT): No

UN "Model Regulation": UN1219, Isopropanol (Isopropyl alcohol), 3, II

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)
Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapor.
H302+H332 Harmful if swallowed or if inhaled.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P302+P352 IF ON SKIN: Wash with plenty of water/...

National regulations

This product is not listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical Substance Inventory. Use of this product is restricted to research and development only. This product must be used by or directly under the supervision of a technically qualified individual as defined by TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

SARA Section 313 (specific toxic chemical listings)

333971-25-8 | Barium tungsten isopropoxide, 10% inisopropanol

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

This product contains barium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Date of preparation / last revision 11/24/2015 / -

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

vPvB: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

NTP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)